

CHECKLIST TO GET A PCB QUOTE

A2.0 ©Copyright Asia Pacific Circuits

Asia Pacific Circuits builds boards to your specifications. We will hold a job if we find any discrepancy between your order and the files and wait for your verification.
Here is a basic checklist of information needed to provide a quote. Please make sure you have indicated:
A part number (including revision number) for your design to ease tracking
Your deadline for order shipment, known as turnaround (short turnaround increases cost)
☐ The quantity of boards required
Board thickness (.062 inches, .032 inches, .093 inches)062 inches is standard
Type of board material (FR4, high-temp FR4, Rogers, Teflon, etc). FR4 is standard
Number of layers
Surface finish (SMOBC, HAL, immersion gold, etc). SMOBC and HAL are standard
The color for solder mask and component overlay. Green is standard
Copper weight on outer layer (1 oz., 2 oz., etc). 1 oz. is standard
Copper weight on inner layers (.5 oz., 1 oz.). Either is standard
The minimum trace and space widths in your design
Indicate your board dimensions on a mechanicalilayer
Do you want your boards to remain panelized, or supplied individually cut?
Files required for bare-board fabrication: Gerber files Drill files IPC-356A (optional)
Files required for SMT assembly: Gerber Files Drill Files X-Y Data Bill of Materials (BOM) in Excel format (for both consigned and turnkey orders).
You can send requests and inquiries To: sales@apc-pcbassembly.com We look forward to serving you.